

Test BG4
2014 Dalton GA
Tech Team written test

Name _____ Company _____

Team Name _____ Contest Position Number _____

Team Member Number _____

Directions: circle the letter preceding the correct answer to each of the following questions: Circle only one answer per question

1. When the barometer falls, this means:
 - a. Gases will diffuse more quickly
 - b. The atmospheric pressure is rising
 - c. It is much easier for explosive gases to build up
 - d. Gases are squeezed into a smaller area

2. Methane is most explosive at what range
 - a. 5% to 15% with at least 12.1% oxygen
 - b. 9.5% to 12.5% with at least 12.1% oxygen
 - c. 5% to 10%
 - d. 9.5% to 10%

3. Electrical malfunctions can produce oxides of nitrogen
 - a. True
 - b. False

4. Usually, the measured distance using a smoke tube is _____ feet
 - a. 100
 - b. 50
 - c. 75
 - d. 25

Test BG4
2014 Dalton GA
Tech Team written test

5. Asphyxiating gases
 - a. Can, in all cases, be tasted, smelled, or seen
 - b. Cause suffocation
 - c. Cause the metal parts of an apparatus to corrode
 - d. Do not produce an oxygen deficient atmosphere

6. The explosive range of hydrogen is _____ to 74.2%
 - a. 7%
 - b. 5%
 - c. 4%
 - d. 3%

7. An anemometer is a small windmill device with a mechanical counter that measures air velocities of over _____ feet per minute
 - a. 100
 - b. 110
 - c. 120
 - d. None of the above

8. Mine ventilation air always moves from _____
 - a. Neutral pressure regions to atmospheric pressure regions
 - b. Low pressure regions to high pressure regions
 - c. High pressure regions to low pressure regions
 - d. Balanced pressure regions to unbalanced pressure regions

9. A partially opened mine door can be used as a regulator
 - a. True
 - b. False

10. The most accurate measurement of air velocity using a smoke tube is obtained by releasing smoke in the center of the airway
 - a. True
 - b. False

Test BG4
2014 Dalton GA
Tech Team written test

11. The mission must always be ended when the low-pressure warning output is at approximately 135 psi
 - a. True
 - b. False

12. The carbon cylinder has a life span of _____years
 - a. 5
 - b. 10
 - c. 15
 - d. 20

13. On the relief valve, the over pressure valve opens between 2-5 mbar
 - a. True
 - b. False

14. A leak in the dosage line can cause low dosage
 - a. True
 - b. False

15. Carbon monoxide contained in the exhaled air is absorbed in the regeneration cartridge
 - a. True
 - b. False

16. When installing a relief valve, turn relief valve 45 degrees to the left
 - a. True
 - b. False

17. High pressure O2 cylinders contain _____% O2
 - a. 96.5
 - b. 97.5
 - c. 98.5
 - d. 99.5

Test BG4
2014 Dalton GA
Tech Team written test

18. When checking the inhalation valve for control function; the pressure gauge must indicate +10 psi
- True
 - False
19. When testing the CO2 absorber the test pressure should be between +7 mbar and + 10 mbar
- True
 - False
20. When checking components (equipment connector and breathing hoses, CO2 Absorber and Breathing air cooler) with the RZ tester, the pressure loss should not exceed 1.5 mbr/min
- True
 - False
21. The maximum drying temperatures for BG4 parts is _____°C
- 50°C
 - 55°C
 - 60°C
 - 65°C
22. The relief valve activation occurs at _____PSI
- 85
 - 86
 - 87
 - 88
23. Dosage output is 1.5 to 1.9 PSI
- True
 - False

Test BG4
2014 Dalton GA
Tech Team written test

24. For units that are in constant use the valve disc on the exhalation and inhalation valves need to be replaced every _____
- a. yearly
 - b. 2 years
 - c. 3 years
 - d. 4 years
25. Drager Safety needs to perform a major overhaul of the pressure reducer every 5 years
- a. True
 - b. False
26. Constant dosage for the BG4 apparatus must be 1.5 to 1.8 L/min
- a. True
 - b. False
27. When checking the minimum valve the admission pressure of the minimum valve must be between _____ and _____ mbar
- a. 0.5 and 2.0
 - b. 0.1 and 1.5
 - c. 1.0 and 2.5
 - d. 0.1 and 2.5
28. To check the relief valve on the BG4; set the pump on positive pressure, pump until relief valve opens, read admission pressure from the pressure gauge and it must be 2 to 7 mbar
- a. True
 - b. False

Test BG4
2014 Dalton GA
Tech Team written test

29. To check the residual warning the cylinder must be closed, observe display unit; the warning must react at approximately 700 psi
- a. True
 - b. False
30. The Panorama Nova mask has a peripheral vision of 95%
- a. True
 - b. False